



#### Display at eye-level

The display is positioned at eye-level to make it easier to read and simplify operation.



#### Optimized air guide plate

The optimized air guide plate reduces temperature deviations inside the system to a minimum.

# MED-340

according to DIN 58345



- **External housing** made from galvanised sheet steel (rust-proof), with white, anti-scratch powder coating. Length of the plug cable: approx. 1.8 m.
- **Adjustable feet** to compensate uneven floors.
- **Interior** made from smooth aluminium with colourless protective coating. Gibs (every 15 mm) for flexible interior arrangement.
- **Interior consists** of nine drawers with stops, on roller runners. There are two adjustable length dividers and nine adjustable cross dividers per drawer. Storage surface per drawer = 0.16 m<sup>2</sup>.
- **Extra-thick 55-mm insulation**, made from high-quality, compression-moulded and environmentally friendly material. Energy saving.
- **Door** with easy-to-replace plastic magnetic seal frame, lockable.
- **Door hinge** on the right-hand side (by default, see illustration), or the left-hand side, can be retrofitted.
- **Forced-air cooling** with cross-flow blower, switches off automatically when you open the door, ensures a uniform temperature and minimizes temperature deviations.

- **Automatic defrosting** with time limit and temperature monitoring.
- **Condensate evaporation** in the refrigerating machine interior.
- **Key switch** protected control panel against tampering. Membrane keyboard with digital temperature display and minimum/maximum temperature memory.
- **Warning functions** with visual and audible alarm signal in the case of temperature deviations and power failure. In the case of power failure, the monitoring unit remains in operation for approx. 72 hours on battery power. Door open alarm after 60 seconds.
- **Alarms** can be forwarded using a potential-free contact (e.g., to a mobile phone with optional GSM-Module or to a control centre).
- **RS485 interface** for connecting to PC-supported temperature documentation (using the optional KIRSCH-PC-KIT).
- **Antifreeze** against sub-zero temperatures.
- **Statically ventilated refrigerating machine**, hermetically sealed, energy saving, low-noise, easy to service.

## Specification

Capacity	330 litres
Temperature setting	approx. +2 °C to +20 °C
Voltage	220 – 240 V, 50/60 Hz
Power consumption	155 watts
Normal consumption	1.20 kWh/24 h
Admissible ambient temperature	from +10 °C to +38 °C
Heat emission (max.)	183 watts
Exterior dimensions (including door handle and distance from wall)	w x d x h = 67 x 63 x 181 cm
Interior dimensions	w x d x h = 53 x 45 x 128 cm (usable depth 5 cm)
Exterior dimensions with door open at 90°	w x d = 67 x 121 cm
Drawer inner dimensions	w x d x h = 50 x 32 x 5.6 cm
Max. load drawer	16 kg
Weight	Net weight 98 kg, gross weight 110 kg

## Optional equipment

- **Glass door with lock.**
- **LED-Illumination** mounted at the top or on side wall.
- **Decorative door frame** for attaching the customer's decorative plates.
- **Equipped with castors.**
- **Drawers on roller runners** (a maximum of twelve drawers is possible).
- **Additional length and cross dividers.**
- **Top drawer can be locked.**
- **Shelf** w x d = 52.7 x 39 cm on rails or overlays (max. load: 40 kg).
- **Condensate container** can be emptied manually if no condensation is required (e.g., in an operating theatre).
- **GSM-Module** for alarm text message transmission (e.g., to a mobile phone).
- **Temperature documentation:**
  - PC-KIT-NET, PC-KIT-USB-MONITORING or PC-KIT-STICK including software for temperature documentation.
  - 4-pin PT 100 or PT 1000 temperature sensor, class 1/3 B, including built-in reference body (measurement bottle or refrigerating block).
  - Mechanical pen-recording thermometer with two waxed paper strips.

**supplyLAB**

www.supplylab.pt  
geral@supplylab.pt

Cacém Park - Edifício 9  
Estrada de Paço de Arcos nº88  
2739-512 Aqualva Cacém  
T +(351) 21 4278700  
F +(351) 21 4278709