



SE-12¹

Aluminum Rotor
12-Place, 14 ml
Tube Dimensions: 18 × 75 mm
Fixed-Angle: 40°
Maximum Speed: 26,000 rpm
K Factor: 335
Rotor Mass: 4.1 kg
Autoclavable: 121°C

	RCF (g)	R (cm)
Max.	70,450	9.33
Min.	28,769	3.81

		RC-28S	RC-26 Plus	RC-24 ²	RC-5C Plus RC-5C ²	RC-5B Plus RC-5B ² RC-5 ²	RC-2B ² RC-2 ²	SS-3 ² SS-4 ²	RC-3B ² RC-3B Plus RC-3C ² RC-3C Plus
SE-12	Max Speed (rpm)	21,000	26,000	24,000	21,000	21,000	21,000	16,000	6,000
	Max RCF (g)	45,959	70,450	60,028	45,959	45,959	45,959	26,679	3,752

Catalog No. 27004

Includes:
SE-12 Rotor
Rotor Cover Assembly **27002**
Cover O-ring **61720**
Rotor Extractor **01031**
Instruction Manual **28505**

TUBES

CAPACITY (ml)		DESCRIPTION	MAX SPEED (rpm)	DIMENSIONS (mm)	TUBE CAT. NO. (Qty/Pkg)	SEALING ASSEMBLY*		ADAPTER REQ'D		NOTES
NOMINAL	FILL					CAT. NO. (Qty/Pkg)	DESCRIPTION	CAT. NO. (Qty/Pkg)	NO. OF PLACES	
14	11	Polypropylene Flanged Tube	24,000	18 × 75	03247 (50)	03269 (50)	Polypropylene, Snap-on	—	—	
14	11	Polycarbonate Flanged Tube	24,000	18 × 75	03246 (50)	03269 (50)	Polypropylene, Snap-on	—	—	
5	5	Pyrex® Tube	5,000	12 × 75	03102 (50)	—	—	00379 (1)	1	
1.5	—	Microtube	—	—	—	—	—	02201 (1)	1	

⁽¹⁾This rotor cover assembly has been tested for microbiological containment (Ref. 1) by PHLS-CAMR, Porton Down.
Suitable for use with materials up to ACDP category 3 (Ref. 2). Seal integrity may be affected by improper use or maintenance.

⁽²⁾Instrument no longer available.

*Sealing Assembly replacement parts may be available. See section E for availability.

All trademarks are the property of their respective owners.

supplyLAB

www.supplylab.pt
geral@supplylab.pt

Cacém Park - Edifício 9
Estrada de Paço de Arcos nº88
2739-512 Aqualva Cacém
T +(351) 21 4278700
F +(351) 21 4278709