


LABEX®-340



Interior protected
Possible static charges are prevented by a dissipation KIRSCH-system.

LABEX® - 340/-468

according to DIN 13221



- **PRO-ACTIVE- Control:** Permanent, proactive monitoring of the performance data and alerts in the case of deviations – so that you can take countermeasures in good time before a fault threatens your chilled goods; world's most accurate temperature control in refrigerated areas thanks to two standard PT-1000 sensors.
- **External housing** made from galvanised sheet steel (rustproof), with white, anti-scratch powder coating. Length of the plug cable: approx. 2.8 m.
- **Adjustable feet** at the front to compensate uneven floors.
- **Interior** made from smooth aluminium with colourless protective coating. Gibs (every 15 mm) for flexible interior arrangement.
- **Interior** of LABEX®-340 consists of two conductive drawers with stops on roller runners and four height adjustable shelves on overlays. There are two adjustable length divider and nine adjustable cross dividers per drawer. Storage surface per drawer = 0.16 m². Interior of LABEX®-468 consists of six shelves on overlays.
- **Extra-thick 55-mm insulation**, made from high-quality, compression-moulded and environmentally friendly material. Energy saving.
- **Self-closing door** with easy-to-replace plastic magnetic seal frame, lockable.
- **Door hinge** on the right-hand side (by default, see illustration), or the left-hand side, can be retrofitted.
- **Forced-air cooling** (axial fan is protected), switches off

- automatically when you open the door, ensures a uniform temperature and minimizes temperature deviations.
- **Automatic defrosting** with time limit and temperature monitoring.
- **Removable condensation container.**
- **Key switch** protected control panel against tampering. Membrane keyboard with digital temperature display and minimum/maximum temperature memory. Control and display sensors protected by safety barriers.
- **Power failure alarm and data recording** (visual and audible alarm), the monitoring unit remains in operation for approx. 72 hours on battery power.
- **Warning functions** with visual and audible alarm signal in the case of temperature deviations or other malfunctions. Door open alarm after 60 seconds.
- **Alarms** can be forwarded using a potential-free contact (e.g., to a mobile phone with optional GSM-Module or to a control centre).
- **Data documentation** can be read via USB interface with KIRSCH Datanet software.
- **Antifreeze** against sub-zero temperatures.
- **Statically ventilated (LABEX®-340) or ventilation-enforced (LABEX®-468) refrigerating machine**, hermetically sealed, energy saving, low-noise, easy to service.
- **Low-noise compressor** reduces noise to 40 dB (corresponds to noise level I; sound perception: whisper, LABEX®-468 only).

Specification

	LABEX®-340	LABEX®-468
Capacity	330 litres	460 litres
Temperature setting	approx. +2 °C to +20 °C	approx. +2 °C to +20 °C
Voltage	220 – 240 V, 50 Hz	220 – 240 V, 50 Hz
Power consumption	128 watts	170 watts
Normal consumption	1.14 kWh/24 h	1.03 kWh/24 h
Admissible ambient temperature	from +10 °C to +38 °C	from +10 °C to +38 °C
Heat emission (max.)	178 watts	280 watts
Exterior dimensions (including door handle and distance from wall)	w x d x h = 67 x 63 x 181 cm	w x d x h = 74 x 75 x 181 cm
Interior dimensions	w x d x h =* 53 x 45 x 128 cm	w x d x h =* 60 x 57 x 128 cm
Exterior dimensions with door open at 90°	w x d = 67 x 121 cm	w x d = 74 x 139 cm
Shelfsize	w x d = 52 x 39 cm	w x d = 59 x 50 cm
Drawer inner dimensions	w x d x h = 50 x 32 x 5.6 cm	w x d x h = 57 x 43 x 5.6 cm
Max. load drawer/shelf	16 kg/40 kg	40 kg
Weight	Net weight 93 kg, gross weight 105 kg	Net weight 112 kg, gross weight 125 kg

*usable depth 5 cm less. (measured values based on Eccol R600a)

Optional equipment

- **Glass door with lock.**
- **Decorative door frame** for attaching the customer's decorative plates.
- **Door fitting** (two pieces required).
- **Equipped with castors.**
- **60 Hz cooling machine upon request**
- **Drawer on roller runners**
LABEX®-340: w x d x h = 50 x 32 x 5.6 cm.
LABEX®-468: w x d x h = 57 x 43 x 5.6 cm.
(a maximum of eleven drawers is possible).
- **Additional length and cross dividers** (for drawer).
- **Additional shelf** on rails or overlays.
- **Basket on rails**
LABEX®-468: w x d x h = 60 x 45 x 10 cm.
- **Aluminium tray** with rails
LABEX®-340: w x d x h = 58.4 x 43 x 2.5 cm.
LABEX®-468: w x d x h = 60 x 45 x 2.5 cm.
- **GSM-Module** for alarm text message transmission (e.g., to a mobile phone).
- **Temperature documentation:** see detailed information on page 48.